

Granite® HFX Cool

Designed for standing seam applications

Granite® HFX Cool organic coated steel is ideal for use with standing seam technology even at low temperature in the cold and wet environments encountered in Northern and Eastern Europe.

- Excellent formability even at low temperatures down to -10°C with similar ductility to pure zinc sheets
- Fully recyclable
- Excellent corrosion resistance
- Allows sophisticated shapes to cover curved, convex or concave surfaces including deep drawing
- Hidden fastenings
- Easy and quick to install, assemble and bend







Standing seam roofs (or walls) use continuous metal panels running from ridge to eaves with interlocking and overlapping 'seams' that offer both excellent weather resistance and distinctive, unbroken visual aesthetics.

Granite® HFX Cool is ideal for these applications because of its ductility and malleability, even at low temperatures, as well as its durability. This allows rapid and effective creation of the seam whether preformed off-site, or formed on site.

Robust and flexible

To meet the requirements of a broad diversity of building projects in various environments. Granite® HFX Cool has an optimised, flexible paint system combined with a flexible steel grade (DX54D 'minimum recommended' and above) that can withstand deformation and weathering. Granite® HFX Cool comes with up to 20 years' guarantee.



PR-LE-COOL-EN - 05/2019 - Published by ArcelorMittal Europe Communications

Performance

Granite® HFX Cool is subject to a battery of tests in the laboratory and at outdoor exposure sites to quarantee the best possible product performance.

Granite® HFX Cool is particularly adapted to harsh climatic environments – mountain or continental climates – with considerable exposure to snow, wind


Granite® HFX Cool is tailor-made for standing seam technologies and can be mechanically or manually

Technical data

Paint coating thickness	Satin: 55 µm Matt: 40 µm
Metallic coating	Z275 g/m2 or equivalent
Thickness	0.55 - 2.0 mm
Width	700 mm to 1500 mm
UV resistance	RUV3 (EN 10169)
Corrosion resistance	RC5 (EN 10169)
Fire resistance	A1 in accordance with EN 13501-1
Guarantee	Up to 20 years

Colours

Granite® HFX Cool is available in 9 colours.









Any questions? Ask them via our contact form on industry.arcelormittal.com/getintouch



industry.arcelormittal.com/samplewebshop



industry.arcelormittal.com/steeladvisor





ArcelorMittal Europe - Flat Products

24-26, boulevard d'Avranches L-1160 Luxembourg industry.arcelormittal.com/granite

Credits

Philippe Vandenameele France PRIVÉ SA – Styl'inov® Savoie Métal Toiture bh-2 / shutterstock.com Communication Design Partnership

Copyright

All rights reserved. No part of this publication may be reproduced in any form or by any means whatsoever, without prior written permission from ArcelorMittal. Care has been taken to ensure that the information in this publication is accurate, but this information is not contractual. Therefore ArcelorMittal and any other ArcelorMittal Group company do not accept any liability for errors or omissions or any information that is found to be misleading.

As this document may be subject to change at any time, please consult the latest information in the product document centre at industry.arcelormittal.com

